

A3 AED



ViVest A3 AED with display *Semi-Automatic*

Easy to use, clear guidance

The 5 inch LCD color-screen will visually instruct the user on what to do and how to do it while the voice guidance of AED-3 helps provide fast, effective and safe preconditions for pre-hospital emergency measures, and guarantees the basic CPR operations of rescuers.

Extremely beneficial for visually impaired and hard of hearing users.

Complete reliability

Daily self-testing, drop tested to 1.5 metres, IP55 protected without the need for a carry case and a failsafe button ensuring the AED is always ready to save lives.

Connectivity ready

Fleet management enabled, messages on status and geo location including movement tracking.

Product model

A3 AED

Size (H x W x D) cms	23.2 x 20.9 x 5.9
Weight Kg	1.5
Protection grade	IP55
Connectivity ready	Yes
Colour display	Yes
Language button	Yes
Child mode	Yes

Product highlights

- Slimline and lightweight - H 23.2 x W 20.9 x D 5.9cm, 1.5KG
- Simple audio and visual instruction for the user with a 5-inch color display
- One of the easiest to use on the market
- Easy language selection between three languages
- Pediatric button to switch the AED into Child Mode (50J)
- Time to shock 7 seconds
- Battery standby life of 5 years (Shelf Life 7 Years) and capable of up to 200 shocks
- Universal Smart Pads lasting 5 years from production (suitable for adults & pediatrics)
- CPR features with metronome
- Algorithm capable of detecting implants such as pacemaker and internal defibrillator
- Automated ECG recording of up to 8 hours
- Daily self testing ensures device is ready for use
- IP55 protects against dust and wet environments
- Drop tested to 1.5 metres
- Shock button has built in failsafe button to alleviate risk of failure
- Able to identify a pulse and make the decision not to shock

Specifications



Defibrillator

Waveform: Biphasic Truncated Exponential (BTE) Waveform

Impedance Range: 20 - 180Ω

Energy Level:

Adults, energy released at 50Ω impedance: 150J.

Child, energy released at 50Ω impedance: 50J

CPR Coaching: CPR instructions are available, with metronome and hand placement instructions

CPR Protocol: Comply with AHA 2020 guideline

Charge/Discharge Time: The time from the initial rhythm analysis to when the shock can be performed: 11 seconds

Arrhythmia Analysis

Accuracy: Comply with IEC60601-2-4

Analysis Time: Typically 7 seconds

Controls

Shock Control: Semi-automatic (press the shock button to deliver energy)

Certification: ISO13485, CE certification

Language Button: Users can switch between primary, secondary and third language among various available language options

Safety Standard:

IEC 60601-1:2005+AMD1:2012+AMD2:2020 CSV

IEC 60601-2-4:2018

IEC 60601-1-2:2014+AMD1:2020 CSV

IEC 60601-1-12:2014+A1:2020 CSV

IEC 60601-1-11:2015+A1:2020

User Interface

Display: A3 AED has a 5 inch color LCD screen, 105 mm (W)x65 mm (BF)

Resolution: 800 x 480 pixels

User Guidance: A3 AED has a colour LCD screen, animation, voice and bilingual text prompts

Volume Adjustment: Volume is adjustable through APP

Device Status Indicator: Visual and audible indicators help to monitor the status of the main device, electrodes, and battery. Flashing green light indicates the device is normal. Flashing red light indicates the device is faulty

Physical Characteristics (including handle)

Height: 232mm

Width: 209mm

Depth: 59mm

Weight: 1.5kg (including battery and pads)

Tolerable Impact/Fall Damage: Can withstand free fall damage from a height of 1.5M onto hard surfaces

Environmental Parameters

Operating/Storage Temperature: -10°C - +50°C

One Hour Operating Temperature Limit (extreme cold): -20°C

Short-term Storage/Transport Temperature: -40°C~+70°C, within one week, with battery and pads uninstalled

Long-term Storage/Transport Temperature: 5°C- 50°C, with battery.

Atmospheric Pressure: 59.4KPa~106KPa

Relative Humidity: 5%~95% (no condensation)

Ingress Protection: IP55

Accessories (Battery)

Type: Lithium manganese dioxide (Li/MnO₂) battery (non-rechargeable), 12V/3000mAh

Capacity: At 20°C±2°C, the new battery can discharge 200±10 times at 150J

Operation Life (standby): 5 years (typical)

Low Battery Status: A battery that indicates low battery can still be used ≥30 times at 150J

Accessories (Pads)

Pads: Suitable for adults and pediatrics.

Shelf Life: 5 years from manufacturing date

Cable Length: 1.1m

Storage Space: Pads can be stored in the space at the back of the device

Data Storage

Memory Type: Internal digital memory

ECG/Event Storage: At least 8 hours of ECG and event/incident recording

Self-test Data Storage: Up to 10 years

Communications

Communications: USB interface, Bluetooth

Overall Device

Date of Production: See label at the bottom of main device

Warranty: 8 years